

Pump Specifications

RH-6J-2216-00 Various RPM

DOUBLE VOLUTE

Performances shown are for cool water and pumps with packing. Horsepower and/or performance adjustments may be required for other seal configurations and to allow for frame and other losses.

HP, efficiency and NPSHR are for full diameter impeller only and may vary somewhat for less than full diameter impellers. See fixed speed curves for more exact data at various speeds and impeller diameters.

Feet x .305 = Meters
 Inches x 25.4 = Millimeters
 GPM x .227 = Cubic Meters/Hour
 GPM x 3.785 = Liters/Minute
 HP x .746 = KW

Speed	Impeller Dia	Style	Solids Dia	N _S	Suction	Discharge	No. Vanes
Various	Various	Enclosed	.75"	2600	8.0	5.0	6

HQ	TRIM	RPM	HQ	TRIM	RPM	HQ	TRIM	RPM	HQ	TRIM	RPM	FULL DIAMETER
A	10.12"-0"	2400	C	10.12"-0"	2000	D	10.12"-0"	1800	E	10.12"-0"	1600	10.12"-0"
B	10.12"-0"	2200		9.56"-0"	2200		9.44"-10"	2000		9.50"-10"	1800	
	9.69"-10"	2400		8.94"-10"	2400		8.81"-10"	2200		8.75"-10"	2000	

